

MATERIAL SAFETY DATA SHEET

Page 1 of 7

Date Prepared: 08/18/04

Date Printed: 12/14/2011

**AIR LINE FLUSH**

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: CP-104 AIR LINE FLUSH  
General or Generic ID: SOLVENT BLEND

Company

Cumberland Products Inc.  
50 Commerce Parkway  
Hodgenville, KY 42748  
1-800-223-1918

Emergency Telephone Number: 1-800-424-9300 CHEMTREC

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by weight)
ACETONE	67-64-1	50.0
ISOPROPANOL	67-63-0	50.0

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

Skin

May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

Swallowing

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury. Exposure causes severe irritation of the gastrointestinal tract.

Inhalation

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms usually occur at air concentrations higher than the recommended exposure limits (See Section 8).

Symptoms of Exposure

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: mouth and throat irritation (soreness, dry or scratchy feeling, cough), stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other central nervous system effects, temporary changes in mood and behavior, muscle weakness, high blood sugar, low blood pressure, mild, temporary changes in the liver, effects on heart rate, respiratory depression (slowing of the breathing rate), loss of coordination, confusion, lung edema (fluid buildup in the lung tissue), kidney damage, coma.

MATERIAL SAFETY DATA SHEET

Page 2 of 7

Date Prepared: 08/18/04

Date Printed: 12/14/2011

**AIR LINE FLUSH**

Target Organ Effects

This material (or a component) shortens the time of onset or worsens the liver and kidney damage induced by other chemicals. Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans. Breathing isopropanol vapors has caused damage to the lining of the middle ear in experimental animals. The relevance of this finding to humans is uncertain. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: mild, reversible liver effects, mild, reversible liver effects, blood abnormalities.

Developmental Information

This material (or a component) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain.

Cancer Information

Based on the available information, this material cannot be classified with regard to carcinogenicity. This material is not listed as a carcinogen by the International Agency for Research on Cancer, the National Toxicology Program, or the Occupational Safety and Health Administration.

Other Health Effects

No data

Primary Route(s) of Entry

Inhalation, Skin absorption, Skin contact, Eye contact, Ingestion.

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Swallowing

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Note to Physicians

This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 3 - Swallowing) when deciding whether to induce vomiting. Acetone (or a component) has produced hyperglycemia and ketosis following substantial ingestion. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions), blood-forming system, kidney. Administration of high doses of isopropanol in combination with known hepatotoxic chemicals resulted in enhanced liver toxicity in experimental animals.\_

**AIR LINE FLUSH****5. FIRE FIGHTING MEASURES**

## Flash Point

-4.0 F (-20.0 C) TCC (Lowest Component)

## Explosive Limit

(for product) Lower 2.0 Upper 12.0 % (Lowest Component)

## Autoignition Temperature

869.0 F (465.0 C) (Lowest Component)

## Hazardous Products of Combustion

May form: carbon dioxide and carbon monoxide.

## Fire and Explosion Hazards

Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

## Extinguishing Media

Alcohol resistant (AR) foam, carbon dioxide, dry chemical.

## Fire Fighting Instructions

Water may be ineffective for extinguishment unless used under favorable conditions by experienced fire fighters. Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning liquid with water used for cooling purposes. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

## NFPA Rating

Health - 1, Flammability - 3, Reactivity - 0

**6. ACCIDENTAL RELEASE MEASURES**

## Small Spill

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

## Large Spill

Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal. Per good environmental management practices, prevent run-off to sewers, streams or other bodies of water. Cover sewer grates and dike the spill. If run-off occurs, notify proper authorities as required, that a spill has occurred. Absorb spilled material on to absorbents. Shovel materials into container. Close container tightly and dispose of properly.

**7. HANDLING AND STORAGE**

## Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Static ignition hazard can result from handling

MATERIAL SAFETY DATA SHEET

Page 4 of 7

Date Prepared: 08/18/04

Date Printed: 12/14/2011

**AIR LINE FLUSH**

and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77. Warning. Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "auto-ignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions.

**Storage**

Small quantities of peroxides may form on prolonged storage. Exposure to light and/or air significantly increase the rate of peroxide formation. If evaporated to a residue, the mixture of peroxides and isopropanol may explode when exposed to heat or shock. Keep containers closed when not in use. Do not store near high heat or open flames.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Eye Protection**

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

**Skin Protection**

Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

**Respiratory Protections**

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

**Engineering Controls**

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

**Exposure Guidelines**

**Component**

**ACETONE (67-64-1)**

OSHA PEL 1000.000 ppm - TWA  
OSHA VPEL 750.000 ppm - TWA  
OSHA VPEL 1000.000 ppm - STEL  
ACGIH TLV 500.000 ppm - TWA  
ACGIH TLV 750.000 ppm - STEL

**ISOPROPANOL (67-63-0)**

OSHA PEL 400.000 ppm - TWA  
OSHA VPEL 400.000 ppm - TWA  
OSHA VPEL 500.000 ppm - STEL  
ACGIH TLV 200.000 ppm - TWA  
ACGIH TLV 400.000 ppm - STEL

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Boiling Range**

133.0 180.0 F (56.1 82.2 C) @ 760 mmHg

MATERIAL SAFETY DATA SHEET

Page 5 of 7

Date Prepared: 08/18/04

Date Printed: 12/14/2011

**AIR LINE FLUSH**

Vapor Pressure

110.0559 mmHg @ 68.00 F

Partial Vapor Pressure

15.7066 mmHg @ 68.00 F

Specific Vapor Density

2.035 @ AIR=1

Specific Gravity

.78 @ 68.00 F

Liquid Density

6.570 lbs/gal @ 68.00 F

.78728 kg/l @ 20.00 C

Percent Volatiles

50.0 %

Total Volatile Organic Compounds (VOC)

100.000 %

787.280 g/l

6.570 lbs/gal

Partial Volatile Organic Compounds (VOC)

50.000 %

392.440 g/l

3.280 lbs/gal

Appearance

TRANSPARENT

State

LIQUID

Physical Form

NEAT

Color

CLEAR, PT-CO COLOR 10 MAX

Odor

SLIGHT ETHANOL/ACETONE-LIKE

pH

No Data

10. STABILITY AND REACTIVITY

Hazardous Polymerization

Product will not undergo hazardous polymerization.

Hazardous Decomposition

May form: carbon dioxide and carbon monoxide.

Chemical Stability

Stable.

Incompatibility

Avoid contact with: acids, aldehydes, alkalis, amines, chlorinated hydrocarbons, ethylene oxide, halogens, isocyanates, strong acids, strong oxidizing agents. Do not

MATERIAL SAFETY DATA SHEET

Page 6 of 7  
Date Prepared: 08/18/04  
Date Printed: 12/14/2011

**AIR LINE FLUSH**

use with aluminum equipment at temperatures above 120 degrees F.

11. TOXICOLOGICAL INFORMATION  
No data

12. ECOLOGICAL INFORMATION  
No data

13. DISPOSAL CONSIDERATION

Waste Management Information  
Dispose of in accordance with all applicable local, state and federal regulations.

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172\_101  
DOT Description:  
PAINT RELATED MATERIAL  
(CONTAINS: ACETONE, ISOPROPANOL),3,UN1263,II

Container/Mode:  
55 GAL DRUM/TRUCK PACKAGE

NOS Component:  
Not applicable

RQ (Reportable Quantity) - 49 CFR 172.101

Product Quantity (lbs)	Component
5000	ACETONE

Other Transportation Information  
The Transport Information may vary with the container and mode of shipment.

15. REGULATORY INFORMATION

US Federal Regulations  
TSCA (Toxic Substances Control Act) Status TSCA (UNITED STATES) The intentional ingredients of this product are listed.

CERCLA RQ - 40 CFR302.4(a)

Component	RQ (lbs)
ACETONE	5000

SARA 302 Components - 40 CFR 355 Appendix A  
None

Section 311/312 Hazard Class - 40 CFR 370.2  
Immediate(X) Delayed(X) Fire(X) Reactive( ) Sudden Release of Pressure( )

SARA 313 Components - 40 CFR 372.65  
None

OSHA Process Safety Management 29 CFR 1910  
None listed

EPA Accidental Release Prevention 40 CFR 68  
None listed

MATERIAL SAFETY DATA SHEET

Page 7 of 7

Date Prepared: 08/18/04

Date Printed: 12/14/2011

**AIR LINE FLUSH**

International Regulations

Inventory Status

AICS (AUSTRALIA) The intentional ingredients of this product are listed.  
CICS (CHINESE) The intentional ingredients of this product are listed.  
DSL (CANADA) The intentional ingredients of this product are listed.  
ECL (SOUTH KOREA) The intentional ingredients of this product are listed.  
EINECS (EUROPE) The intentional ingredients of this product are listed.  
ENCS (JAPAN) The intentional ingredients of this product are listed.  
IECSC (CHINA) The intentional ingredients of this product are listed.  
PICCS (PHILIPPINES) The intentional ingredients of this product are listed.  
SWISS (SWITZERLAND) The intentional ingredients of this product are listed.

State and Local Regulations

California Proposition 65

The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986: This product contains the following substance(s) known to the state of California to cause cancer.  
BENZENE

The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986: This product contains the following substance(s) known to the state of California to cause reproductive harm.  
BENZENE

New Jersey RTK Label Information

ACETONE	67-64-1
ISOPROPYL ALCOHOL	67-63-0

Pennsylvania RTK Label Information

2-PROPANONE	67-64-1
2-PROPANOL	67-63-0

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.