

M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT NAME: Amber Rust Proofing (Aerosol)
PRODUCT CODE: 980

Date Printed: 5/8/2006
Page 1 of 2

MATERIAL SAFETY DATA SHEET

CP-980 AMBER RUST PROOFING

NFPA CODES: H F R P

PRODUCT CODE: CP-980

2 3 0 B

PRODUCT NAME: Amber Rust Proofing

HMIS CODES: H F R P

2 2 0 B

SECTION I - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components (Specific Chemical Identity, Common Name(s))

	CAS #	OSHA PEL	ACGIH TLV	STEL	%
PETROLEUM DISTILLATES	64742-88-7	100 ppm	100 ppm		10-30
*HEXANE	110-54-3	50 ppm	50 ppm		55-65
PROPANE/ISOBUTANE	68476-86-8	800 ppm	800 ppm		10-30

SEE INSTRUCTIONS PAGE 3.

DOT SHIPPING - CONSUMER COMMODITY ORM-D

SECTION II - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT - Range: -40 to 315 F

SPECIFIC GRAVITY (H₂O= 1): 0.73

VAPOR PRESSURE PSIG@ 70 F: 45-55

MELTING POINT - Liquid: NA

VAPOR DENSITY (Air = 1): HEAVIER THAN AIR

EVAPORATION RATE (Water = 1): Greater

SOLUBILITY IN WATER: Negligible

APPEARANCE AND ODOR: Thin Brown Liquid/Solvent Odor

SECTION III - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method Used): -142.5 TCC

FLAMMABLE LIMITS

LEL

UEL

: NA

: NA

EXTINGUISHING MEDIA - Use water fog, dry chemical or carbon dioxide

SPECIAL FIRE FIGHTING PROCEDURES - Fire fighters should wear NIOSH approved positive pressure self-contained breathing apparatus. Aerosol cans may rupture when heated.

UNUSUAL FIRE AND EXPLOSION HAZARDS - Heated cans may burst.

SECTION IV - REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: Heat, sparks, and open flames.

INCOMPATIBILITY (Materials to Avoid): Strong Acids, Alkalis, Oxidizers

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Carbon Dioxide, Carbon Monoxide, Other Products of Incomplete Combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION V - HEALTH HAZARD DATA

ROUTES OF ENTRY: Inhalation, Skin, Ingestion

HEALTH HAZARDS (Acute and Chronic) - May cause dizziness or narcosis in high vapor concentrations. Will cause defatting of skin. Effects are reversible. Long-term exposure (years) to vapor may cause lung, liver, or kidney damage. The solvents listed have been reported to affect the central nervous system: TOLUENE

M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT NAME: Amber Rust Proofing (Aerosol)
PRODUCT CODE: 980

Date Printed: 5/8/2006
Page 2 of 2

CARCINOGENICITY - None listed.

SIGNS AND SYMPTOMS OF EXPOSURE - Inhalation - Difficulty in breathing. Skin - Redness. Ingestion: Vomiting. Alcohol consumed before or after exposure may increase adverse effects. Over exposure may cause dizziness and loss of concentration.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE - See attachment page 3.

EMERGENCY AND FIRST AID PROCEDURES - Give oxygen - do not induce vomiting - gastric lavage - wash eyes and skin with water. Remove to fresh air, contact physician immediately.

SECTION VI - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED - Use absorbent sweeping compound to soak up material. Pour into container. Dispose as hazardous waste.

WASTE DISPOSAL METHOD - Dispose of waste in accordance with applicable Federal, State and Local requirements.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING - Keep away from heat, sparks or open flame. Store at temperatures below 120 F.

OTHER PRECAUTIONS - Avoid prolonged breathing of vapors. Always use with adequate ventilation.

SECTION VII - CONTROL MEASURES

RESPIRATORY PROTECTION (Specify Type) -- Self-contained breathing apparatus if above TLV limits are exceeded.

VENTILATION - Local Exhaust

PROTECTIVE GLOVES - None required if spraying.

EYE PROTECTION - Safety glasses or goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT - Long sleeves and long pants or coveralls.

WORK/HYGIENIC PRACTICES - Do not smoke while using. Wash hands after use. Concentrated vapors of this product are heavier than air and will collect in low areas, pits, storage tanks and other confined spaces. Do not enter these areas.

Avoid breathing of vapors.

Keep out of reach of children.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain damage and nervous system damage. Intentional misuse by concentrating and inhaling this product may be harmful or fatal.

If you have a medical condition, consult with a physician prior to using this product.

ATTACHMENT SHEET:

* Starred items are subject to the reporting requirements of Sara 313 and 40 CFR 372. If any of the components in Section 1 are preceded by a star (*), you must notify each person to whom this product is sold.

State of California Proposition 65. The following listed chemicals are known to the State of California to cause cancer and/or reproductive toxicity: TOLUENE

New Jersey Right to Know: See Section I

ADDITIONAL INFORMATION:

%VOC: 79.9% #/GAL

VOC: 4.86 #/GAL

The information contained in this document is believed to be accurate and offered in good faith as typical values, but is not warranted as such. Each user should confirm prior to use, the accuracy and suitability of this information and determine whether it is appropriate for the intended use. If you sell this product under your own label, you must prepare your own MSDS with your own name, address and telephone number and must by law accompany each shipment.